

PERFORMANCE TO LAST BUILT







**FH+10** SERIES



















- 24" High Sides
- 6'-9-1/2" and 6'-1-1/2" Inside Bed Widths
- 8" Cold Formed I Beam Frame

- Aluminum Tool Box w/Storage
- Scissors Hoist on 12' and 14' Lengths
- 11 Gauge Diamond Plate Fenders



**Aluminum Tool Box** with Storage Area (steel box on gooseneck)



**Heavy Duty** Adjustable Coupler (4 bolt)



**Scissors Hoist** Standard on 12' & 14' (cylinder on 10')



Step for Bed Access



**Tarp Option** 



**Aluminum Ramps** 



Hydraulic Jack Option



**Gate Hold Backs** 



Trip Lever Option



8" I Beam Frame



1/8" Fenders



trip lever (forward pull)

jack upgrade

jack upgrade wireless remote

pallet fork holders

spare tire & wheel **COLORS** 

**Bumper Pull** 

14'

81-1/2"

## STANDARD SPECIFICATIONS

sidewalls & floor	10 gauge (thickness of steel)		
height of sidewall	24"		
width inside body	73-1/2" & 81-1/2"		
frame	8" cold formed I-beam		
tool box	aluminum diamond plate w/storage area		
gate	double acting with metering chains		
fenders	1/8" steel diamond plate		
hydraulic lift	scissors hoist 12' & 14' - cylinder 10'		
hydraulic pump	power up/power down		
suspension	rubber ride (low maintenance)		
brakes	electric (all wheels)		
tires & wheels	9950 GVWR - 15" 8 ply rated - 6 bolt		
(all tires are radial)	12000 & 14000 GVWR 16" 10 ply rated		
	8 bolt		
jack	7000 lb. 10' & 12' - 10000 lb. 14'		
coupler	2-5/16" adjustable (4 bolt)		
safety chains	3/8" with latch hook		
lights & wiring	LED lights & sealed wire harness		
aluminum ramps	15-1/2" wide x 72" long		
warranty	2 year limited (see warranty for details)		
other standard features	step to access inside bed		
	d-rings inside bed		
	gate hold back latches		
OPTIONS			
available rating	9950, 12000, 14000 & 16000 GVWR		
pintle ring			
tarp			
stake pockets			

for tailgating

pulls and all goosenecks)

black - red - charcoal

operates hydraulics wirelessly

7k to 10k (10k standard on 14' bumper

hydraulic jack (power up/power down)

D	U	Ν	1	Ρ	В	0	D	Y	V	O	L	U	Ν	1	Ε	

# **AXLE SPECIFICATIONS** (rubber ride suspension)

length	width	volume (cubic yard)
10'	73-1/2"	4.5
10'	81-1/2"	5
12'	81-1/2"	6
14'	81-1/2"	7

GVWR	axle
9950	6000 lb - 6 bolt - electric brakes & easy lube spindles
12000	6000 lb - 8 bolt - electric brakes & easy lube spindles
14000	7000 lb - 8 bolt - electric brakes & easy lube spindles
16000	8000 lb - 8 bolt - electric brakes & oil bath hubs

## **FRAME & BODY SPECIFICATIONS**

n/a

frame & tongue	body sides & floor	body cross members	body main rails	fenders
8" @ 10 lb/ft I-beam (cold formed)	10 gauge	3" channel	2" x 3" x 3/16" tube	1/8" diamond plate

## **WEIGHT SPECIFICATIONS by GVWR (gross vehicle weight rating)**

4140 lbs

3980 lbs

length width 9950 GVWR 12000 GVWR 14000 GVWR 16000 GVWR width 12000 GVWR 14000 GVWR 16000 GVWR length 73-1/2" 3140 lbs 3400 lbs 10' n/a n/a n/a n/a n/a n/a n/a 10' 81-1/2" 3420 lbs 3580 lbs n/a n/a n/a n/a n/a n/a n/a 12' 3580 lbs 3840 lbs 3990 lbs 4410 lbs 4430 lbs 4590 lbs 5010 lbs 81-1/2" 12' 81-1/2"

4560 lbs

Gooseneck

14'

81-1/2"

4740 lbs

4900 lbs

5320 lbs

